

sewoo

Robust and durable label mobile printers

LK-P30II



- Fast Print Speed
- Excellent Compatibility
- Quick and easy to support peel mode
- Rugged design for Drop resistant
- Durable and resistant to water and dust
- S-MDM (SSM & SCM)
- Accessories : Shoulder Strap, Car Charger



WiFi



Bluetooth



Barcode



Portable



Durable



Rugged Design



Drop Resistant



Easy Loading



Fast Speed



Compact Design



Easy Maintenance



Improved Battery Life



S-MDM Support



APPLICATION



SPECIFICATIONS



PRINTER CHARACTERISTICS

Print Method
Direct thermal

Print Speed
Up to 3,9ips (100mm/sec)

Print Width
Up to 2.8" (72mm)

Resolution
203 dpi (8dots/mm)

Memory
8MB SDRAM,
16MB(Max.32MB) Flash

Battery Voltage / Capacity
7.4V / 2600mAh.
Rechargeable Li-ion battery

Battery Charge Time
3.3Hrs

Standby Time
100Hrs

Sensor
Paper end, Black mark,
Cover open, Gap

Reliability
TPH life : 50km



PHYSICAL CHARACTERISTICS

Dimension (W x D x H)
4.72"×5.98"×2.75"
(120×152×70mm)

Weight
1.4lb(640g with Battery)



INTERFACES

Standard
USB,Serial(RS-232C)

Option
Wi-Fi(802.11a/b/g/n),
Bluetooth Smart Ready
(Bluetooth4.2+BLE)



CERTIFICATIONS

KC, CE, FCC, IC, UL/cUL,
Mfi, UKCA,BCS,CCC



OPERATING CHARACTERISTICS

Operating Temperature
14 ~ 122°F(-10 ~ 50°C)

Operating Humidity
10 ~ 80%

Storage Temperature
-4 ~ 140°F(-20 ~ 60°C)

Storage Humidity
10 ~ 90%

Dust-and Water-resistance Rating
IP42(Set only), IP54(With case)

Drop Rating
3.9ft(1.2m, Set only), 5.9ft(1.8m, With case)



BARCODES

1D
EAN-8, EAN-8(+2+5), EAN-13,
EAN-13(+2+5), Codabar, Code11,
Code39, Code93, Code128, ITF,
LUPC-A(+2+5), UPC-E, UPC-E(+2+5),
Planet, UPC-A etc

2D
QR, PDF417, MicroPDF417, Maxicode,
Datamatrix, Aztec, RSS14, TLC39



SOFTWARE

Emulations
ESC/POS, CPCL, ZPL/EPL Command
compatible

Drivers
Windows Driver(XP ~, Server2003 ~),
Window CE & Mobile Driver & SDK
(CE 4.2~, Mobile 5.0~), Linux Driver,
Mac Driver, OPOS Driver,
JavaPOS Driver, iOS SDK,
Android(6.0 ~) SDK



MEDIA CHARACTERISTICS

Media Type
Thermal paper/label

Media Width
0.9"~ 3.1"(25~80mm)

Media Core Diameter
Ø 0.4" (12.5mm)

Media Roll Diameter
Ø 2.2"(56mm)

Thickness
0.06 ~ 0.16mm



FONTS / GRAPHICS

Character Type
Font A(12×24), Font B(9×17),
Asian Font(KOR,JPN,CHN-GB2312,
CHNBig5), Font0/1/2/4/5/6/7,
Resident TTF, Downloadable TTF,
FontA~H, FontGS, Residnt TTF(Font0),
Font 1~8

Characters per Line (CPL)
Font A(12x24): 48cpl,
Font B(9x17): 64cpl,

Character Set
95 Alphanumeric,
14 International,
128 x 18 Graphic



ACCESSORIES

Standard
USB Cable, Battery Pack, Serial Cable
Thermal Roll Paper, Belt Buckle,
Battery Charger (8.4V)

Optional
Battery Cradle, Vehicle Charger,
Leather Case, Shoulder Trap,
MSR, IC Card Reader

sewoo

Republic of Korea [Head Office / R&D Center]

28-6, Gajangsaneopdong-ro, Osan-si, Gyeonggi-do, 18103, Republic of Korea
T. +82-31-8077-5000 F. +82-31-624-5310 E. sales@miniprnter.com

www.miniprnter.com

USA, Inc.

Torrance, CA 90502, USA
T. +1-310-617-7401
E. NA_sales@miniprnter.com

México Office

Cuauhtémoc, D.F. Mexico. CP 06500
T. +52-1-55-3232-9543 M. +52-1-55-143893
E. LA_sales@miniprnter.com

China Office

Shang hai shi, Song jiang qu
T. +86-177-1729-9100
E. sales@miniprnter.com

